

JUMBO TUBE SKID FOR GAS STORAGE AND TRANSPORTATION

WITH YEARS OF EXPERIENCES, SRISEN ENERGY CAN SUPPORT DIFFERENT SOLUTIONS FOR GAS TRANSPORTATION TO CUSTOMER.

CNG AND INDUSTRIAL GAS TUBE TRAILER ARE SUITABLE FOR TRANSPORTING BIG AMOUNT OF CNG OR OTHER INDUSTRIAL GAS TO PLACES WHERE GAS PIPE NETWORKS ARE NOT CONSTRUCTED .

MAIN MODEL:

NEW DESIGN: DIA 711MM 34FT LENGTH TUBE (40FT CONTAINER)

NEW DESIGN: DIA 711MM 8 TUBES 40FT



MODEL NO.	SR7-3000-CNG-25
TUBE QUANTITY(PIECE)	7
FILLING MEDIA	CNG
EMPTY WEIGHT(KG)	27400
CNG LOADING WEIGHT(KG)	4438
FULL LOAD WEIGHT(KG)	31838
CNG LOADING VOLUME(NM ³)	6342
WATER CAPACITY (M ³)	21
LEAKING TEST PRESSURE(MPA)	25
BURST TEST PRESSURE(MPA)	37.5
WORKING TEMPERATURE(°C)	-40~60
SAFETY DEVICE DIA.(MM)	≧Ø20
FILLING CONNECTOR DIA.(INCH)	1
CONTAINER DIMENSION(LXWXH IN MM)	12192X2438X2300

MODEL NO.	SR8-3000-CNG-25
TUBE QUANTITY(PIECE)	8
FILLING MEDIA	CNG
EMPTY WEIGHT(KG)	30850
CNG LOADING WEIGHT(KG)	5072
FULL LOAD WEIGHT(KG)	35922
CNG LOADING VOLUME(NM ³)	7248
WATER CAPACITY (M ³)	24
LEAKING TEST PRESSURE(MPA)	25
BURST TEST PRESSURE(MPA)	37.5
WORKING TEMPERATURE(°C)	-40~60
SAFETY DEVICE DIA.(MM)	≧Ø20
FILLING CONNECTOR DIA.(INCH)	1
CONTAINER DIMENSION(LXWXH IN MM)	12192X2438X2300

NEW DESIGN WITH LARGER VOLUME AND LESS CONNECTION, CARRY MORE GAS, LESS MAINTENANCE.



DIA 559MM 10 TUBES 40FT

DIA 559MM 11 TUBES 40FT

MODEL NO.	SR10-2400-CNG-25
TUBE QUANTITY(PIECE)	10
FILLING MEDIA	CNG
EMPTY WEIGHT(KG)	30250
CNG LOADING WEIGHT(KG)	5070
FULL LOAD WEIGHT(KG)	35320
CNG LOADING VOLUME(NM ³)	7240
WATER CAPACITY (M ³)	24
LEAKING TEST PRESSURE(MPA)	25
BURST TEST PRESSURE(MPA)	37.5
WORKING TEMPERATURE(°C)	-40~60
SAFETY DEVICE DIA.(MM)	≧Ø20
FILLING CONNECTOR DIA.(INCH)	1
CONTAINER DIMENSION(LXWXH IN MM)	12192X2438X2000

MODEL NO.	SR11-2400-CNG-25
TUBE QUANTITY(PIECE)	11
FILLING MEDIA	CNG
EMPTY WEIGHT(KG)	32950
CNG LOADING WEIGHT(KG)	5577
FULL LOAD WEIGHT(KG)	38527
CNG LOADING VOLUME(NM ³)	7972
WATER CAPACITY (M ³)	26.4
LEAKING TEST PRESSURE(MPA)	25
BURST TEST PRESSURE(MPA)	37.5
WORKING TEMPERATURE(°C)	-40~60
SAFETY DEVICE DIA.(MM)	≧Ø20
FILLING CONNECTOR DIA.(INCH)	1
CONTAINER DIMENSION(LXWXH IN MM)	12192X2438X2000



JUMBO TUBE SKID FOR GAS STORAGE AND TRANSPORTATION



DIA 559MM 12 TUBES 20FT



DIA 711MM 9 TUBES 20FT

MODEL NO.	SR12-1040-CNG-25
TUBE QUANTITY(PIECE)	12
FILLING MEDIA	CNG
EMPTY WEIGHT(KG)	20760
CNG LOADING WEIGHT(KG)	2640
FULL LOAD WEIGHT(KG)	23400
CNG LOADING VOLUME(NM ³)	3768
WATER CAPACITY (M ³)	12.48
LEAKING TEST PRESSURE(MPA)	25
BURST TEST PRESSURE(MPA)	37.5
WORKING TEMPERATURE(°C)	-40~60
SAFETY DEVICE DIA.(MM)	≥Ø20
FILLING CONNECTOR DIA.(INCH)	1
CONTAINER DIMENSION(LXWXH IN MM)	6300X2438X2000

MODEL NO.	SR9-1700-CNG-25
TUBE QUANTITY(PIECE)	9
FILLING MEDIA	CNG
EMPTY WEIGHT(KG)	21900
CNG LOADING WEIGHT(KG)	3240
FULL LOAD WEIGHT(KG)	25140
CNG LOADING VOLUME(NM ³)	4620
WATER CAPACITY (M ³)	15.3
LEAKING TEST PRESSURE(MPA)	25
BURST TEST PRESSURE(MPA)	37.5
WORKING TEMPERATURE(°C)	-40~60
SAFETY DEVICE DIA.(MM)	≥Ø20
FILLING CONNECTOR DIA.(INCH)	1
CONTAINER DIMENSION(LXWXH IN MM)	6300X2438X2300




CNG GROUND STORAGE

CNG GROUND STORAGE CAN BE WIDELY USE FOR STORE NATURAL GAS IN NGV STATION, INDUSTRIAL FACTORY, NATURAL POWER PLANT ETC.

NOTE: EXCEPT THE ABOVE MENTIONED MODEL, WE CAN DESIGN AND MANUFACTURE ACCORDING TO CUSTOMER'S REQUIREMENTS.

MAIN SPECIFICATION:



MODEL		WORKING PRESSURE (MPA)	WATER CAPACITY (M3)	LOADING VOLUME (NM3)	DIMENSION(MM)	TARE WEIGHT(KG)
	SR3-1290-25	25	3.87	1141	6640X668X2158	6500
	SR3-1440-25	25	4.32	1274	7350X668X2158	6900
	SR3-2250-25	25	6.75	1991	11250X668X2158	10200
	SR4-1290-25	25	5.16	1522	6640X1335X1494	8100
	SR4-1440-25	25	5.76	1699	7350X1335X1494	9200
	SR4-2250-25	25	9.00	2655	11250X1335X1494	13300
	SR5-1290-25	25	6.45	1902	6640X1335X2158	12100
	SR5-1440-25	25	7.20	2124	7350X1335X2158	13800
	SR5-2250-25	25	11.25	3318	11250X1335X2158	19900